

MODEL

GC0518 系列

高速针送料平缝机

High speed needle bar feed lockstitcher

GC0518

GC0518-H

GC0518-B

GC0518-AD3

GC0518-HD

GC0518-BD






GC0518A-D 自动剪线高速针送料平缝机

本系列机型采用连杆式针送料机构，连杆挑线，旋梭勾线，构成双线锁式线迹。上下轴用螺旋伞齿轮传动，圆盘式针距调节机构，杠杆式倒顺缝机构，全自动润滑。针送料方式使送料特性更加稳定，缝料层之间不会产生滑移。高低速缝纫，倒顺缝针距误差极小，可广泛适用于衬衫，服装厂缝制丝绸、尼龙化纤等类似薄料织物。

GC0518A-D 型采用电子伺服电机，数字电路控制，具有自动剪线，自动定针位，自动定针数等数项自动缝纫模式，性能稳定，操作效率极高。

Link type needle feed, link thread take-up and thread catching by rotary hooks are incorporated in the machine to produce lockstitch. The arm shaft and hook shaft are driven by bevel gears. It features knob-type stitch regulator, lever-type reverse feeding mechanism and automatic lubrication. Needle feed motion permits more stable feeding and can prevent shifting in layers. It guarantees minimum stitch length variation when sewing mode changing between high speed and low speed or between forward feeding and reverse feeding. It is available for stitching silk, nylon, synthetic fabrics, etc.

GC0518A-D is designed with electronic servo motor, digital circuit control and automatic sewing modes such as auto trimming, auto needle positioning and auto stitch presetting. It features stable and efficient sewing performance.



主要技术参数 Main technical specifications

| 型号 Model | 最高缝速 Max sewing speed | 线迹长度 Stitch length | 针杆行程 Needle bar stroke | 压脚提升 Presser foot lift | 机针 Needle size | 旋梭 Rotating hook | 润滑方式 Lubrication | 电动机 Motor |
|-------------|--------------------------|-----------------------|---------------------------|--|--|---|-------------------------|---|
| GC0518 | 5000 r.p.m. | 4 mm | 31.8 mm | 手动 / 膝控 By hand / knee 5 / 11 mm | DB × 1 11 [#] -14 [#] | 自动润滑旋梭 Auto lubricated hook | 自动润滑 Auto lubricated | 370 瓦缝纫机 专用电机 370 W Clutch motor |
| GC0518-H | 3500 r.p.m. | 5 mm | 33 mm | | DP × 5 18 [#] | 自动润滑旋梭 Auto lubricated hook | 自动润滑 Auto lubricated | |
| GC0518-B | 3000 r.p.m. | 5 mm | 35 mm | | DP × 5 22 [#] | 自动润滑大旋梭 Auto lubricated large hook | 自动润滑 Auto lubricated | |
| GC0518-AD3 | 5000 r.p.m. | 4 mm | 31.8 mm | | DB × 1 14 [#] | 自动润滑剪线旋梭 Auto lubricated hook for trimmer | 自动润滑 Auto lubricated | 220 伏 550 瓦 伺服电机 220V 550W Servo motor |
| GC0518-HD | 3500 r.p.m. | 5 mm | 33 mm | | DP × 5 18 [#] | | 自动润滑 Auto lubricated | |
| GC0518-BD | 3000 r.p.m. | 5 mm | 35 mm | | DP × 5 22 [#] | 自动润滑剪线大旋梭 Auto lubricated large hook for trimmer | 自动润滑 Auto lubricated | |